

RoHS COMPLIANT

HDMI-AM-DF-V1A

1. Description:

HDMI-AM-DF-V1A is a simple HDMI Type A Male to Micro HDMI Type D Female pass-through adapter breakout board. It brings all 20 pins of a HDMI Type A Male and a Micro HDMI Type D Female connector to screw terminal blocks and headers for easy testing, prototyping and breadboard connection. All 20 pins of the Female connector directly connect to the Male connector. User can also use the two 10 pins headers on both sides of the breakout board to connect to breadboard or prototype PCB.

2. Features:

- All 20 pins of a HDMI Type A Male and a Micro HDMI Type D Female connector brought out to headers and screw terminal blocks
- All 20pins of a HDMI Type A Male connector directly connect to a Micro HDMI Type D Female connector.
- Various connecting method chosen by users.
- 1.00"(25.4mm)X1.18"(30mm) board dimensions




Figure 1: Parts inside the kit (Note: the module is not assembled, user can decide which connector to use on the module.)

3. Parts:

- 1) 1pc X HDMI-AM-DF-V1A PCB
- 2) 1pc X HDMI Type A Male Connector
- 3) 1pc X Micro HDMI Type D Female Connector
- 4) 2pc X 10pin 0.1"(2.54mm) spacing terminal block
- 5) 1pc X 20pin 0.1"(2.54mm) header




Figure 2: Example of connecting the HDMI-AM-DF-V1A on a proto PCB (Note: This picture only shows the pins spacing, actual use may not be used on a breadboard)












Figure 4: HDMI-AM-DF-V1A with terminal blocks

Related products from eLabGuy:



HDMI-DF-DM-V1A



HDMI-AF-DF-V1A



HDMI-AF-DM-V1A



HDMI-DF-DF-V1A